



▶ Sleep mode

This function ensures you to have a sweetly sleep, without suffering a under-cooling or over-heating experience at night.

Independent Directional Louver



8-way air outlets

Other Function

▶ ECO Energy-saving



By pressing ECO button AC will automatically run with suitable temperature to cut most energy than normal model.

▶ Filter-cleaning Reminder



The indicator for filter-clean reminder will be lighted after a 500 hours running time of the unit.

▶ 8-way Air Outlets



Brand new outlook and panel design, top discharge air outlet, 360° air supply with extra comfort.

▶ Wi-Fi Control*



You can easily control your air conditioner anywhere with your Wifi Connection.

*: Optional

Standard Features:

- Independent Dehumidification
- 24H Timer
- Filter Check
- Auto Mode
- Sleep Mode
- ECO
- Display On/Off
- Horizontal Manual Swing
- Auto-Restart
- Self-troubleshooting
- Fire-proved Electrical Box

Optional Features:

- Celsius And Fahrenheit Degree Switch
- Healthy Filter
- WIFI Control

Parameters 1							
Mode		Ph-V-Hz	5K	6K	8K	10K	12K
Power supply			1Ph, 115V~, 60Hz	1Ph, 115V~, 60Hz	1Ph-115V-60Hz	1Ph-115V-60Hz	1Ph-115V-60Hz
Cooling	RATED Capacity	Btu/h	5000	6000	8000	10,000	12,000
	RATED EER	Btu/h,w/w	11.0	12.2	12.1	12.1	12.1
	RATED Input	W	451	492	661	826	992
	RATED Current	A	3.9	4.3	5.8	7.3	8.6
Indoor noise level (Hi/Med/Lo)	dB(A)		55/-/50	55/52/50	58/56/53	59/56/54	59/57/55
Power Cord Length	mm		1980	1980	1980	2500	2500
Power Cord Length	ft		6.5	6.5	6.5	8.2	8.2
Control type			Mechanical	Remote Control	Remote Control	Remote Control	Remote Control
Dimension(W*D*H)	mm		406x386x318	472x396x338	472x440x338	502x546x372	502x546x372
	in		15.98x15.2x12.52	18.58x15.59x13.31	18.58x17.32x13.31	19.76x21.5x14.6	19.76x21.5x14.6
Packing (W*D*H) 1A package	mm		455x428x378	543x444x378	543x486x378	555x601x441	555x601x441
	in		17.9x16.9x14.6	21.37x17.48x14.88	21.38x19.13x14.88	21.85x23.66x17.36	21.85x23.66x17.36
Packing (W*D*H) 6A package	mm		486x465x435	570x480x435	570x520x435	600x640x480	600x640x480
	in		19.13x18.31x17.13	22.44x18.9x17.13	22.44x20.47x17.13	23.62x25.2x18.9	23.62x25.2x18.9
Net/Gross weight 1A package	Kg		18/20	20/23	23/26	29/33	33/37
	lbs		39.68/44.09	44.09/50.71	50.71/57.32	63.93/72.75	72.75/81.57
Gross weight 6A package	Kg		23.0	27.6	30.8	39.0	42.0
	lbs		50.7	60.8	68	86.0	92.6
Loading quantity 20' /40' /40'HQ 1A package	Pieces		390/810/940	312/648/754	264/576/670	185/390/468	185/390/468
Loading quantity 20' /40' /40'HQ 6A package	Pieces		285/600/720	220/480/574	220/440/526	108/228/285	108/228/285
Stacking layers			8	8	8	6	6
Window Opening	Width(Min/Max)(Inches)	in	23/36	23/36	23/36	26/36	26/36
		mm	584/914	584/914	584/914	660/914	660/914
	Height(Min)(Inches)	in	14.5	14.5	14.5	16	16
		mm	368	368	368	406	406

Parameters 2						
Mode		Ph-V-Hz	15K	18K	22K	24K
Power supply			1Ph, 115V, 60Hz	1Ph, 230/208V, 60Hz	1Ph, 230/208V, 60Hz	1Ph, 230/208V, 60Hz
Cooling	RATED Capacity	Btu/h	15,000	18000 /17600	22000/21600	24000/23600
	RATED EER	Btu/h,w/w	11.9	11.9	10.4	10.4
	RATED Input	W	1261	1513/1479	2116/2078	2308/2270
	RATED Current	A	11.0	7.1/6.6	10.2/9.3	11.0/10.1
Indoor noise level (Hi/Med/Lo)	dB(A)		56/53/52	57/54/52	60/58/56	60/58/56
Power Cord Length	mm		2500	1800	1800	1800
Power Cord Length	ft		8.2	5.9	5.9	5.9
Control type			Remote Control	Remote Control	Remote Control	Remote Control
Dimension(W*D*H)	mm		600x645x455	600x645x455	671x682x476	671x682x476
	in		23.6x25.4x17.9	23.6x25.4x17.9	26.4x26.9x18.7	26.4x26.9x18.7
Packing (W*D*H) 1A package	mm		652x754x505	652x754x505	740x780x513	740x780x513
	in		25.67x29.69x19.88	25.67x29.69x19.88	29.2x30.7x20.2	29.2x30.7x20.2
Packing (W*D*H) 6A package	mm		690x780x565	690x780x565	790x820x550	790x820x550
	in		27.17x30.71x22.24	27.17x30.71x22.24	31.1x32.28x21.65	31.1x32.28x21.65
Net/Gross weight 1A package	Kg		48/53	53/58	56/61	59/64
	lbs		105.82/116.85	116.85/127.87	123.46/134.48	130.07/141.10
Gross weight 6A package	Kg		61.8	65.4	70.8	74.8
	lbs		136.2	144.2	156.0	162.7
Loading quantity 20' /40' /40'HQ 1A package	Pieces		96/216/268	96/216/268	84/188/233	84/188/233
Loading quantity 20' /40' /40'HQ 6A package	Pieces		92/196/196	92/196/196	56/112/120	56/112/120
Stacking layers			6	6	6	6
Window Opening	Width(Min/Max)(Inches)	in	28/41	28/41	30/41	30/41
		mm	712/1041	712/1041	762/1041	762/1041
	Height(Min)(Inches)	in	19	19	19.5	19.5
		mm	483	483	495	495

Remarks: All information shown above is subject to change without prior notice. Please refer to our sales representatives for more details.