

DEA SERIES

Dehumidifier

Features



Built in handle



Compact Size
High Dehumidifying Capacity



Easy Movable
Water Tank



Optional Button Control

- Humidistat to set a comfortable room humidity and energy saving
- Tank control system, indicator lit when tank is full
- Top mounted control panel
- Approved for use in drying/laundry cabins
- Anti-frost protection for ultra low temperature use
- Continuous drainage
- Quiet operation

Parameters

Model		DEA 30E	DEA 50E	DEA 70E	DEA 70EP
Power supply	V-Ph-Hz	115V- 60Hz, 1Ph	115V- 60Hz, 1Ph	115V- 60Hz, 1Ph	115V- 60Hz, 1Ph
Moisture removal	Pints/day	30	50	73	73
Rated input	W	295	490	730	730
Rated current	A	2.6	4.5	6.9	6.9
Control type		Electronic Control	Electronic Control	Electronic Control	Electronic Control
Water tank volume	Pint	7.4	7.4	13.7	13.7
Noise level (Hi/Lo)	dB(A)	50/47	51/48	53/49	53/49
RH Range Manual		35%-80%RH	35%-80%RH	35%-80%RH	35%-80%RH
Ambient temp	°C	5-32	5-32	5-32	5-32
	°F	41°F-90°F	41°F-90°F	41°F-90°F	41°F-90°F
Dimension (W*D*H)	mm	370x270x490	370x270x490	382x305x640	382x305x640
	in	14.57x10.63x19.29	14.57x10.63x19.29	15.04x12.01x25.20	15.04x12.01x25.20
Packing (W*D*H) 3A package	mm	415x320x535	415x320x535	445x360x670	445x360x670
	in	16.34x12.60x21.06	16.34x12.60x21.06	17.52x14.17x26.38	17.52x14.17x26.38
Net/Gross weight 3A package	Kg	15.6/17.2	15.6/17.2	19.40/21.36	20.49/22.43
	lb	34.39/37.92	34.39/37.92	42.86/47.09	45.22/49.45
Loading quantity 20' /40' /40'HQ 3A package	Pieces	376/788/1010	376/788/1010	237/492/595	237/492/595

* All information above is subject to change without prior notice, please refer to our sales representatives for more details.